



**FIBERFOX EBC15 fiber optic cable terminated with expanded beam plug 2CH**

- protection class: IP68 (up to 6m)
- core diameter: 50µm (multimode)
- operating temperatur: -40°C bis +70°C
- mating cycles: 5000

2x transparent shrink tube loose on both sides.  
unshrunk for customized self-labeling before shrinking.

All FIBERFOX connectors meet the MIL-DTL-83526 standard.  
FIBERFOX cable plugs are hermaphroditic, means no distinction in male in female. Two- and four-channel systems can be mixed.

Description	Stock-Code	Length	Weight
NKO2M3-FX-0-005 airspool	1027401	5 m	0,33 kg
NKO2M3-FX-0-010 airspool	1027402	10 m	0,45 kg
NKO2M3-FX-0-020 airspool	1027403	20 m	0,69 kg
NKO2M3-FX-0-050 airspool	1027404	50 m	1,41 kg
NKO2M3-FX-0-100 airspool	1027405	100 m	2,61 kg
NKO2M3-FX-0-150 airspool	1027406	150 m	3,81 kg
NKO2M3-FX-0-250 airspool	1027407	250 m	6,21 kg
NKO2M3-FX-2-050 cable reel	1027408	50 m	3,01 kg
NKO2M3-FX-2-100 cable reel	1027409	100m	4,21 kg
NKO2M3-FX-2-150 cable reel	1027410	150 m	5,41 kg
NKO2M3-FX-2-250 cable reel	1027411	250 m	10,26 kg

No.	Part	Qty.
1	Expanded beam plug 2ch MM cable 6mm plug	2
2	TD-04G50-OM3-MIL	1
3	Shrink Tube Ø 6,4 -> 3,2 unshrunked	2

Sheet Number 1/1	Projection 	Scale 1:2	Format A4	Tolerancing ISO 2768- m	
g	cm <sup>2</sup>	cm <sup>3</sup>	Created	HeBo	10.06.2021
Material			Modified		
Material addition			Approved	DiRo	10.06.2021
Description NKO2M3-FX FIBERFOX EBC15 cable 2CH MM OM3			ECN Number		
NEUTRIK			Status	FOR FINAL	
3D Model ID			Document ID	Revision 01	